

Typ/ Ausführung	Scheiben- dicke (mm)	Mittenloch-ø (mm) Radseitig	Lochzahl/ Lochkreis- (mm) / Mittenloch-ø (mm) Fahrzeugseitig	Scheiben-ø (mm)	Rad- last (kg)	Abroll- umfang (mm)	Gültig ab Herstell- datum			
40.A3	15	30.301	56,9	3/112 / 57,1	140	500	1965	09/2003		
			58,0 - 58,5	4/98 / 58,1 - 67,1	135	530	1860	10/1997		
			54,0 - 60,0	4/100 / 54,1 - 67,0	135	590	1935	10/1997		
		30.005	56,9	4/106 / 57,1	140	800	2300	06/2007		
			57,0 - 65,0	4/108 / 57,1 - 70,0	145	530	1860	10/1997		
			60,0 - 67,0	4/114,3 / 60,1 - 67,1	155	530	1860	10/1997		
			80,0	4/160 / 80,1	205	400	1860	10/1997		
			58,0 - 58,5	5/98 / 58,1 - 58,6	135	530	1860	10/1997		
			54,0 - 57,0	5/100 / 54,1 - 70,0	135	530	1860	10/1997		
		30.374	60,0 - 67,0	5/108 / 60,1 - 67,1	145	930	2300	11/2010		
			66,8	5/108 / 66,9	150	930	2300	11/2010		
			65,0	5/110 / 65,1 - 70,0	147	930	2300	11/2010		
			57,0 - 66,5	5/112 / 57,1 - 70,0	145	930	2300	11/2010		
			57,0 - 66,4	5/112 / 57,1 - 66,6	165	930	2300	11/2010		
			SO 3441	66,4	5/112 / 66,6	150	1000	2400	02/2013	
	16	60,0 - 71,5	5/114,3 / 60,1 - 71,6	155	930	2300	11/2010			
		30.355	64,9	5/120 / 65,1	165	900	2300	06/2007		
		30.010	72,4	5/120 / 72,6	155	900	2300	06/2007		
			72,5 - 74,0	5/120 / 72,6 - 74,1	155	900	2300	06/2007		
			73,6	5/120,65 / 73,8	155	615	1935	10/1997		
		30.206	71,5	5/130 / 71,6	168	800	2220	39/2013		
			65,9	6/114,3 / 66,1	155	900	2330	10/2005		
		30.409	17,5	59,9	4/104 / 60,1	140	590	1935	07/2005	
		30.395		56,9	4/106 / 57,1	140	800	2300	06/2007	
		30.411		56,9	5/112 / 57,1	150	930	2300	11/2010	
		30.401		66,4	5/112 / 66,6	165	930	2300	11/2010	
		30.398		72,4	5/120 / 72,6	155	900	2300	06/2007	
30.357	25	64,9	5/120 / 65,1	165	615	1935	09/2003			
40.A4	20	30.396	58,0 - 58,5	4/98 / 58,1 - 67,1	135	590	1935	10/1997		
			54,0 - 60,0	4/100 / 54,1 - 67,0	135	590	1935	10/1997		
			56,9	4/106 / 57,1	140	800	2300	06/2007		
		30.375	57,0 - 65,0	4/108 / 57,1 - 70,0	145	530	1860	10/1997		
			60,0 - 67,0	4/114,3 / 60,1 - 67,1	155	530	1860	10/1997		
			58,0 - 58,5	5/98 / 58,1 - 58,6	135	530	1860	10/1997		
			54,0 - 57,0	5/100 / 54,1 - 70,0	135	530	1860	10/1997		
			60,0 - 67,0	5/108 / 60,1 - 67,1	145	930	2300	11/2010		
			66,8	5/108 / 66,9	150	930	2300	11/2010		
		30.345	65,0	5/110 / 65,1 - 70,0	147	930	2300	11/2010		
			57,0 - 66,5	5/112 / 57,1 - 70,0	145 - 165	930	2300	11/2010		
			60,0 - 71,5	5/114,3 / 60,1 - 71,6	155	930	2300	11/2010		
			30.356	64,9	5/120 / 65,1	165	900	2300	06/2007	
			30.097	72,4	5/120 / 72,6	155	900	2300	06/2007	
				72,5 - 74,0	5/120 / 72,6 - 74,1	155	900	2300	06/2007	
	30.345	73,6	5/120,65 / 73,8	155	615	1935	10/1997			
		71,6	5/130 / 71,5	164	600	2100	10/1997			
		71,5	5/130 / 71,6	167	800	2220	01/2014			
		65,9	6/114,3 / 66,1	155	900	2330	10/2005			
		40.A5	30.674	23	71,5	5/130 / 71,6	167	800	2220	01/2014
			25	71,6	5/130 / 71,5	164	800	2100	10/1997	
	30.346	71,5	5/130 / 71,6	167	800	2220	01/2014			
40.A6		30	71,6	5/130 / 71,5	164	800	2100	10/1997		
40.A7		35	71,6	5/130 / 71,5	164	800	2100	10/1997		